



## Micromax II Deck Light - 19 Flash Patterns



### Specifications

Lens: Polycarbonate  
 Weight: 0,170 KG  
 Current Draw: 12V ~ 1.4 Amps

### Dimensions

Width: 240 mm  
 Depth: 37 mm  
 Height: 39 mm

### Part N° Voltage Colour

DKLED812A	12		Amber
DKLED824A	24		Amber
DKLED812B	12		Blue
DKLED824B	24		Blue

## Micromax II Dash Light - 25 Flash Patterns



### Specifications

Lens: Polycarbonate  
 Weight: 0,2 KG  
 Current Draw: 12V ~ 1.4 Amps

### Dimensions

Width: 240 mm  
 Depth: 117 mm  
 Height: 39 mm

### Part N° Voltage Colour

DLED812A	12		Amber
DLED824A	24		Amber
DLED812B	12		Blue
DLED824B	24		Blue



[www.cell2solutions.com](http://www.cell2solutions.com)

# cell<sup>2</sup>solutions

**PowerLED Range** designed to handle the adverse conditions you face everyday.



LED3

XTREME

PAR36

DECK

DASH



FOR MORE INFORMATION PLEASE CALL CELL2SOLUTIONS ON

(0034) 664 600 602

cell<sup>2</sup>solutions

Cell2Solutions  
c/Peña Beza, Nave 23,  
Poligono de Silvota,  
Aebunias, 33192,  
ESPAÑA (Spain)





## LED3 - 12 Flash Patterns



### Specifications

Lens: Polycarbonate  
 Weight: 0,1 KG  
 Current Draw: 12V ~ 350 mA

### Dimensions

Width: 99 mm  
 Depth: 41 mm  
 Height: 35 mm

### Part N° Voltage Colour

LED3 3A12	12		Amber
LED3 3A24	24		Amber
LED3 3R12	12		Red
LED3 3R24	24		Red
LED3 3B12	12		Blue
LED3 3B24	24		Blue

## LED6 - 12 Flash Patterns



### Specifications

Lens: Polycarbonate  
 Weight: 0,270 KG  
 Current Draw: 12V ~ 700 mA

### Dimensions

Width: 99 mm  
 Depth: 72 mm  
 Height: 35 mm

### Part N° Voltage Colour

LED6 6A12	12		Amber
LED6 6A24	24		Amber
LED6 6R12	12		Red
LED6 6R24	24		Red
LED6 6B12	12		Blue
LED6 6B24	24		Blue

## LED4 - 19 Flash Patterns



### Specifications

Lens: Polycarbonate  
 Weight: 0,13 KG  
 Current Draw: 12V ~ 700 Amps

### Dimensions

Width: 122 mm  
 Depth: 41 mm  
 Height: 35 mm

### Part N° Voltage Colour

LED4 4A12	12		Amber
LED4 4A24	24		Amber
LED4 4R12	12		Red
LED4 4R24	24		Red
LED4 4B12	12		Blue
LED4 4B24	24		Blue

## Optional mounting brackets



### Part N° To suit LED

MB03S	LED3
MB04S	LED4
MB06S	LED6
MB36S	LED36 (adjustable)

## High intensity LED Warning Lights ECE65 and EMC approved

### Specifications

Cell2solutions' high intensity **Power LED** range offers superb optical quality, is tough and durable and offers many years of maintenance free service.

- High intensity LEDs.
- 'Waterproof' with sealed for life electronics.
- Built-in selectable flash patterns can be alternating and synchronous.
- Very low Power Consumption.
- Available in Amber, Red and Blue.
- ECE and EMC approved.
- Available in 12v and 24v.
- Tough and reliable.





## PowerLED Linear Xtreme6



### Specifications

Lens: Polycarbonate  
 Body: Aluminium Coated Black  
 Current Draw: 0,70 Amps  
 Weight: 240g

*Dimensions*  
 Width: 148 mm  
 Depth: 30 mm  
 Height: 55 mm

Part N°	Voltage	Colour
XLED6A12	12	Amber
XLED6A24	24	Amber
XLED6B12	12	Red
XLED6B24	24	Red
XLED6R12	12	Blue
XLED6R24	24	Blue

## PowerLED Linear Xtreme6 Dual



### Specifications

Lens: Polycarbonate  
 Body: Aluminium Coated Black  
 Current Draw: 0,70 Amps  
 Weight: 440g

*Dimensions*  
 Width: 165 mm  
 Depth: 30 mm  
 Height: 95 mm

Part N°	Voltage	Colour
XLED-D-6A12	12	Amber
XLED-D-6A24	24	Amber
XLED-D-6B12	12	Red
XLED-D-6B24	24	Red
XLED-D-6R12	12	Blue
XLED-D-6R24	24	Blue

## Optional mounting brackets



### Xtreme L Bracket

L Shaped Bracket for the Power LED Xtreme warning light range.

### Xtreme Adjustable Bracket

Adjustable Bracket for the Power LED Xtreme warning light range.



## Xtreme High Intensity LED warning Lights

### Applications

Cell2solutions' high intensity **Power LED Linear Xtreme** range is suitable for many vehicle applications including road maintenance, refuse trucks, utilities, delivery vehicles and road safety.

### Specifications

- New wider angle beam for improved safety.
- Ultra bright 3rd generation LEDs.
- 19 selectable flash patterns.
- Multiple units can be synchronised.
- Epoxy sealed for life electronics.
- E approved.
- Available in 12v and 24v.
- Very low power consumption.
- Tough cast aluminium base and polycarbonate lens.
- Extreme temperature reliability.





## PAR36/7 - 7 LEDs



### Specifications

Lens: Polycarbonate  
Weight: 0,250 KG  
Current Draw: 12V ~ 800 mA

#### Dimensions

Diameter: 165 mm  
Depth: 30 mm

Part N°	Voltage	Colour
PAR36/7A12	12	Amber
PAR36/7A24	24	Amber
PAR36/7R12	12	Red
PAR36/7R24	24	Red
PAR36/7B12	12	Blue
PAR36/7B24	24	Blue

## PAR36 High Intensity LED warning Lights

### Mounting Options

- Surface Mount as standard.
- Grommet Mount as optional.

Adjustable  
L Shaped  
Rubber Grommet

### Applications

Cell2solutions' high intensity **Power LED PAR36** range is suitable for many vehicle applications including road maintenance, refuse trucks, utilities, delivery vehicles and road safety.

### Specifications

- 7 Wide angle linear LED's
- 19 Flash Patterns
- 12v and 24v
- Does not require separate flasher unit
- Just 165mm(h) x 30mm(d) x 165mm(w)
- Can be wired to flash alternately in synchronisation
- Grommet mount available
- Slimline design makes ideal for grille, fender and covert applications

## PAR36/10 - 10 LEDs



### Specifications

Lens: Polycarbonate  
Weight: 0,250 KG  
Current Draw: 12V ~ 900 mA

#### Dimensions

Diameter: 165 mm  
Depth: 30 mm

Part N°	Voltage	Colour
PAR36/10A12	12	Amber
PAR36/10A24	24	Amber
PAR36/10R12	12	Red
PAR36/10R24	24	Red
PAR36/10B12	12	Blue
PAR36/10B24	24	Blue

